

Stratasys® J35™ Pro

The Stratasys® J35™ Pro 3D printer combines the quality of Stratasys PolyJet technology with a compact, office-friendly design.

The three material channel, multi material printer features a rotating build platform with fixed print head for outstanding surface finish and print quality. Engineered for the office or design studio environment, it features a small footprint and ProAero™ filtration technology for odor free, silent and low power operation.

The J35 Pro offers a streamlined design-to-print workflow powered by GrabCAD Print™. This allows users to import their designs using native CAD files or 3MF file formats.

Remote monitoring lets you easily manage your print jobs from outside the office. Additionally, water jet removable support makes post processing simple and enables the creation of complex parts without compromising accuracy or detail.

Product Specifications

Model Materials	<ul style="list-style-type: none"> VeroUltra™ ClearS VeroUltra™ BlackS VeroUltra™ WhiteS 	<ul style="list-style-type: none"> Vero™ ContactClear DraftGrey™ Digital ABS Plus™ 	<ul style="list-style-type: none"> Elastico™ Black Elastico™ Clear
Support Materials	SUP710™ / Water Soluble Support – WSS™150		
Build Size/Printing Area	Round Print Tray with up to 1,174cm ² (182 in ²) Print Height: 158mm* (6.22 in.)*		
Layer Thickness	Horizontal build layers down to 18 microns (0.0007 in.)		
Network Connectivity	LAN - TCP/IP		
System Size and Weight	651 x 661 x 774mm (25.63 x 26.02 x 30.48 in.); 98 kg (216 lbs.)		
Operating Conditions	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)		
Power Requirements	100–240 VAC, 50–60 Hz, 10A, 1 phase		
Regulatory Compliance	CE, FCC, EAC, cTUVus, CB, RCM		
Operator Attendance	Limited attendance for job start and job stop required		
Software	GrabCAD Print		
Build Modes	High Quality Speed (HQS) – 18.75um		
Accuracy	<p>Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – ±150μ; above 100 mm – ±0.15% of part length.**</p> <p>Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm – ±180μ; above 100 mm – ±0.2% of part length.**</p>		
Additional features	<ul style="list-style-type: none"> Long Print Mode (allowing cartridge Hot Swap for selected material) Notifications for user via email and GC APP Internal camera VoxelPrint (per order) 		

* The printable height is 158 mm (6.22 in.) and the max printable model height is 155 mm (6.1 in.).

** Measured when ambient temperature is 23 °C and relative humidity is 50%.

USA - Headquarters

7665 Commerce Way
Eden Prairie, MN 55344, USA
+1 952 937 3000

ISRAEL - Headquarters

1 Holtzman St., Science Park
PO Box 2496
Rehovot 76124, Israel
+972 74 745 4000

stratasys.com

ISO 9001:2015 Certified

© 2023 Stratasys. All rights reserved. Stratasys, the Stratasys Signet logo, PolyJet, GrabCAD, J35, VeroUltra, DraftGrey, Digital ABS Plus, Elastico, and Vero are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries and affiliates. All other trademarks are the property of their respective owners. Product specifications subject to change without notice. PSS_PJ_J35_Pro_A4_0423a

EMEA

Airport Boulevard B 120
77836 Rheinmünster, Germany
+49 7229 7772 0

ASIA PACIFIC

7th Floor, C-BONS International Center
108 Wai Yip Street Kwun Tong Kowloon
Hong Kong, China
+ 852 3944 8888

Energy Group

3D Printing Solutions for Industry

a SolidWorld Group company

FORNITORE CERTIFICATO

stratasys Σ NACT METAL

info line 051 864519 | www.energygroup.it

